

COMPANY IDENTITY: PACKAGING SERVICE CO., INC.  
PRODUCT IDENTITY: CROWN LACQUER THINNER NEXT  
NEW MSDS DATE: 06/21/06

DATE: 06/21/06  
PAGE 1 OF 5

## MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1. THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

PRODUCT IDENTITY: CROWN LACQUER THINNER NEXT  
COMPANY IDENTITY: PACKAGING SERVICE CO., INC.  
COMPANY ADDRESS: 1904 MYKAWA ROAD  
COMPANY CITY: PEARLAND, TX 77581  
COMPANY PHONE: 1-281-485-1458  
CHEMTREC PHONE: 1-800-424-9300

### SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

#### CONTAINS:

85-95% ACETONE (67-64-1)[200-662-2],  
Proprietary soy-based blend

Specific chemical identities will be made available to medical professionals and others as required by 29 CFR 1910.1200 (i)(iv).

Number in parentheses is CAS #, number in brackets is European EC #.

LVL01

### SECTION 3. HAZARDS IDENTIFICATION

#### RISK STATEMENTS:

R12 Extremely Flammable.  
R36/37/38 Irritating to eyes, respiratory system and skin.

#### SAFETY STATEMENTS:

S9 Keep container in a well-ventilated place.  
S16 Keep away from sources of ignition. No smoking.

### SECTION 4. FIRST AID MEASURES

**EYE CONTACT:** For eyes, flush with plenty of water for 15 minutes & get medical attention.

**SKIN CONTACT:** In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

**INHALATION:** After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped give artificial respiration.

**SWALLOWING:** If swallowed, get immediate medical advice. Inducing vomiting may cause aspiration into the lungs.

LVL01

### SECTION 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** NFPA Class B extinguishers(Carbon Dioxide or foam)for Class I B liquid fires.

**SPECIAL FIRE FIGHTING PROCEDURES:** Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear.

**COMPANY IDENTITY:** PACKAGING SERVICE CO., INC.  
**PRODUCT IDENTITY:** CROWN LACQUER THINNER NEXT  
**NEW MSDS DATE:** 06/21/06

**DATE:** 06/21/06  
**PAGE 2 OF 5**

(Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES:** EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**CONTAINMENT TECHNIQUES:** Keep unprotected personnel away. Wear appropriate personal protective equipment given in Section 8. Ventilate spill area. Stop spill at source. Dike & contain.

**CLEAN-UP PROCEDURES:** Clean up remainder with absorbent materials. Mop up & dispose of. Persons without proper protection should be kept from area until cleaned up.

**OTHER PRECAUTIONS:** Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone.

## SECTION 7. HANDLING AND STORAGE

**HANDLING:** Isolate from oxidizers, heat, sparks, electric equipment & open flame. Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

**STORAGE:** Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone. Do not store above 49 C/120 F. Store large amounts in structures made for OSHA Class I B liquids. Keep container tightly closed & upright when not in use to prevent leakage.

LVLTO1

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

**RESPIRATORY EXPOSURE CONTROLS:** A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

### VENTILATION:

LOCAL EXHAUST: Necessary  
MECHANICAL (GENERAL): Acceptable  
SPECIAL: None  
OTHER: None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

**PERSONAL PROTECTIONS:** Wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

**WORK & HYGIENIC PRACTICES:** Provide readily accessible eye wash stations & safety showers. Wash at end of each workshift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

### SECTION 9. PHYSICAL DATA

APPEARANCE :	Liquid, Water-White
ODOR :	Ketone
BOILING RANGE :	56 59 225* C / 133 139 437* F (*=End Point)
AUTO IGNITION TEMPERATURE :	398 C / 750 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	2.5
FLASH POINT (TEST METHOD):	-16 C / 2 F (TCC)
FLAMMABILITY CLASSIFICATION:	Class I B
GRAVITY @ 68/68 F / 20/20 C :	
API :	43.4
SPECIFIC GRAVITY (Water=1) :	0.809
POUNDS/GALLON :	6.738
VOC'S (>0.44 Lbs/Sq In) :	91.1 Vol. % / 736.6 g/L / 6.135 Lbs/Gal
TOTAL VOC'S (TVOC) :	96.0 Vol. % / 769.3 g/L / 6.408 Lbs/Gal
NONEXEMPT VOC'S (CVOC) :	0.0 Vol. % / 0.0 g/L / 0.000 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS) :	0.0 Wt. % / 0.0 g/L / 0.000 Lbs/Gal
VAPOR PRESSURE (mm of Hg)@20 C	183.1
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)	0.0
VAPOR DENSITY (air=1) :	2.1
WATER ABSORPTION :	Appreciable
REFRACTIVE INDEX :	1.360

### SECTION 10. STABILITY & REACTIVITY

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Isolate from oxidizers, heat, sparks, electric equipment & open flame.

**MATERIALS TO AVOID:** Isolate from strong oxidizers such as permanganates, chromates & peroxides.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide, Carbon Oxides from burning.

**HAZARDOUS POLYMERIZATION:** Will not occur.

LVLTO1

### SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS #	TWA (OSHA)	TLV (ACGIH)	HAP
Acetone	67-64-1	1000 ppm	500 ppm A4	No

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

MATERIAL	CAS #	CEILING	STEL (OSHA/ACGIH)
Acetone	67-64-1	None Known	750 ppm

### ACUTE HAZARDS

**EYE & SKIN CONTACT:** Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

**INHALATION:** Anesthetic. Irritates respiratory tract. Acute overexposure can cause serious nervous system depression. Vapor harmful.

**SWALLOWING:** Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

COMPANY IDENTITY: PACKAGING SERVICE CO., INC.  
PRODUCT IDENTITY: CROWN LACQUER THINNER NEXT  
NEW MSDS DATE: 06/21/06

DATE: 06/21/06  
PAGE 4 OF 5

**SUBCHRONIC HAZARDS/CONDITIONS AGGREGATED**

**CONDITIONS AGGREGATED:** Persons with severe skin, liver or kidney problems should avoid use.

**CHRONIC HAZARDS**

**CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:** This product has no carcinogens listed by IARC, NTP, NIOSH, OSHA or ACGIH, as of this date, greater or equal to 0.1%.

**SECTION 12. ECOLOGICAL INFORMATION**

**MAMMALIAN INFORMATION:**

<b>MATERIAL</b>	<b>CAS #</b>	<b>LOWEST KNOWN LETHAL DOSE DATA</b>
Acetone	67-64-1	LOWEST KNOWN LD50 (ORAL) 5340.0 mg/kg(Rabbits)
Acetone	67-64-1	LOWEST KNOWN LC50 (VAPORS) 21000 ppm (Cats)
Acetone	67-64-1	LOWEST KNOWN LD50 (SKIN) 20000.0 mg/kg (Rabbits)

**AQUATIC ANIMAL INFORMATION:** The most sensitive known aquatic group to any component of this product is: Mosquito Fish 13000 ppm or mg/L (48 hour exposure).

**MOBILITY:** This material is a mobile liquid.

**DEGRADABILITY:** This product is completely biodegradable.

**ACCUMULATION:** Bioaccumulation of this product has not been determined.

**SECTION 13. DISPOSAL CONSIDERATIONS**

Processing, use or contamination may change the waste management options. Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If in doubt, contact appropriate agencies.

**SECTION 14. TRANSPORT INFORMATION**

IF CONTAINER HAS > PRODUCT RQ (SEE SECTION 15) PUT "RQ," BEFORE SHIPPING NAME.

DOT SHIPPING NAME: Paint Related Material, 3, UN1263, PG-II

DRUM LABEL: (FLAMMABLE LIQUID)

IATA / ICAO: Paint Related Material, 3, UN1263, PG-II

IMO / IMDG: Paint Related Material, 3, UN1263, PG-II

EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

LVLTO1

**SECTION 15. REGULATORY INFORMATION**

**EPA REGULATION:** SARA SECTION 311/312 HAZARDS: Acute Health, Fire

All components of this product are on the TSCA list. This material contains no known products restricted under SARA Title III, Section 313 in amounts greater or equal to 1%.

<b>SARA TITLE III INGREDIENTS</b>	<b>CAS#</b>	<b>WT. % (REG. SECTION)</b>	<b>RQ(LBS)</b>
Acetone	67-64-1	>91 (311,312)	5000

> 5439 LB / 2472 KG OF THIS PRODUCT IN 1 CONTAINER EXCEEDS THE "RQ" OF ACETONE. Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate

**COMPANY IDENTITY:** PACKAGING SERVICE CO., INC.  
**PRODUCT IDENTITY:** CROWN LACQUER THINNER NEXT  
**NEW MSDS DATE:** 06/21/06

**DATE:** 06/21/06  
**PAGE** 5 OF 5

state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

**STATE REGULATIONS:** THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

**INTERNATIONAL REGULATIONS:** The components of this product are listed on the chemical inventories of the following countries: Australia, Canada, Europe (EINECS), Japan, Korea, United Kingdom.

## **SECTION 16. OTHER INFORMATION**

### **HAZARD RATINGS:**

HEALTH (NFPA): 1    HEALTH (HMIS): 2    FLAMMABILITY: 3,    REACTIVITY: 0

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

**EMPLOYEE TRAINING:** Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

**NOTICE:** The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process. Unless updated, this Material Safety Data Sheet is valid until 06/21/2009.