

COMPANY IDENTITY: PACKAGING SERVICE CO., INC
PRODUCT IDENTITY: CROWN PAINT THINNER NEXT
NEW MSDS DATE: 11/09/2007

DATE: 11/09/07
PAGE 1 OF 1

MATERIAL SAFETY DATA SHEET

This Material Safety Data Sheet conforms to the requirements of ANSI Z400.1, using the International Chemical Safety Cards of the Global Harmonizing System. THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) IMPORTANT: Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers, & users of this product.

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY

PRODUCT IDENTITY: CROWN PAINT THINNER NEXT
COMPANY IDENTITY: PACKAGING SERVICE CO., INC.
COMPANY ADDRESS: 1904 MYKAWA ROAD
COMPANY CITY: PEARLAND, TX 77581
COMPANY PHONE: 1-281-485-1458
CHEMTREC PHONE: 1-800-424-9300

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

CONTAINS:

30-40% PETROLEUM DISTILLATE (64742-47-8),
Number in parentheses is CAS #, number in brackets is European EC #.

WBPTO1

SECTION 3. HAZARDS IDENTIFICATION

RISK STATEMENTS:

R36/37/38 Can be Irritating to eyes, respiratory system and skin.
R65 Harmful: may cause lung damage if swallowed.

SAFETY STATEMENTS:

S2 Keep out of the reach of children.
S23 Do not breathe gas, fumes, vapor, or spray.
S24 Avoid contact with skin.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or product label.

SECTION 4. FIRST AID MEASURES

EYE CONTACT: For eyes, flush with plenty of water for 15 minutes & get medical attention.

SKIN CONTACT: In case of contact with skin immediately remove contaminated clothing. Wash thoroughly with soap & water. Wash contaminated clothing before reuse.

INHALATION: After high vapor exposure, remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR).

SWALLOWING: Rinse mouth. Do NOT induce vomiting. GET MEDICAL ATTENTION IMMEDIATELY. Do NOT give liquids to an unconscious or convulsing person.

SECTION 5. FIRE FIGHTING MEASURES

FIRE & EXPLOSION PREVENTIVE MEASURES: Material will not ignite or support combustion under conditions of normal use. No flash point to boiling. (>200°F)

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE MEASURES: Avoid unnecessary contact. Can dry and / or irritate skin. Filter respirator for organic vapors if very long term extreme contact is expected.

CONTAINMENT AND CLEAN-UP MEASURES: Stop spill at source. Dike and contain. Absorb remaining liquid in sand or inert absorbent. Do NOT wash away into sewer.

SECTION 7. HANDLING AND STORAGE

HANDLING: Isolate from oxidizers, Use only with adequate ventilation. Avoid breathing of vapor or spray mist. Avoid contact with skin & eyes. Wear OSHA Standard goggles or face shield if handling for extended or prolonged periods. Consult Safety Equipment Supplier. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse. Continue all label precautions!

STORAGE: Isolate from strong oxidants. Do not store above 49 C / 120 F. Keep container tightly closed & upright when not in use to prevent leakage.

WBPTO1

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

RESPIRATORY EXPOSURE CONTROLS: A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z86.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use.

VENTILATION:

LOCAL EXHAUST: Necessary
MECHANICAL (GENERAL): Acceptable
SPECIAL: None
OTHER: None

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

PERSONAL PROTECTIONS: Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

WORK & HYGIENIC PRACTICES: Provide readily accessible eye wash stations & safety showers. Wash at end of each work shift & before eating, smoking or using the toilet. Promptly remove clothing that becomes contaminated. Launder or discard contaminated clothing.

SECTION 9. PHYSICAL DATA

APPEARANCE :	Liquid, Milky-White
ODOR :	Mild
BOILING RANGE :	100 114 206* C / 212 238 403* F (*=End Point)
AUTO IGNITION TEMPERATURE :	260 C / 500 F (Lowest Component)
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	0.9 (Lowest Component)
FLASH POINT (TEST METHOD):	> 212(TCC) – NO FLASH TO BOIL
FLAMMABILITY CLASSIFICATION:	N/A
GRAVITY @ 68/68 F / 20/20 C:	
API :	20.9
SPECIFIC GRAVITY (Water=1) :	0.90 – 0.93
POUNDS/GALLON :	7.4 – 7.9
VOC'S (>0.44 Lbs/Sq In) :	0.0 Vol. % / 0.0 g/L / 0.000 Lbs/Gal
TOTAL VOC'S (TVOC) :	32.5 Vol. % / 254.5 g/L / 2.119 Lbs/Gal
NONEXEMPT VOC'S (CVOC) :	32.5 Vol. % / 254.5 g/L / 2.119 Lbs/Gal
HAZARDOUS AIR POLLUTANTS (HAPS) :	0.0 Wt. % / 0.0 g/L / 0.000 Lbs/Gal
VAPOR PRESSURE (mm of Hg)@20 C	16.8
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C)0.0	
VAPOR DENSITY (air=1) :	0.8
WATER ABSORPTION :	Appreciable
REFRACTIVE INDEX :	NA

SECTION 10. STABILITY & REACTIVITY

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Isolate from oxidizers, heat, & open flame.

MATERIALS TO AVOID: Reacts with strong oxidants, causing fire & explosion hazard.

COMPANY IDENTITY: PACKAGING SERVICE CO., INC
PRODUCT IDENTITY: CROWN PAINT THINNER NEXT
NEW MSDS DATE: 11/09/2007

DATE: 11/09/07
PAGE 3 OF 3

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION: Will not occur.

WBPTO1

SECTION 11. TOXICOLOGICAL INFORMATION

MATERIAL	CAS #	TWA (OSHA)	TLV (ACGIH)	HAP
PETROLEUM DISTILLATES	64742-47-8	5 mg/m ³	35 mg/m ³	No

This product contains no EPA Hazardous Air Pollutants (HAP) in amounts > 0.1%.

MATERIAL	CAS #	CEILING	STEL (OSHA/ACGIH)
		None Known	None Known

ACUTE HAZARDS:

Eyes Primary irritation index (rabbit): 1.0 (Maximum score is 110.)
Skin Primary irritation index (rabbit): 0.4 (Maximum score is 8.0.)
Acute dermal LD50 (rabbit): 6,000 - 12,000 mg/kg
Inhalation Acute 4 hours (rat): > 6 mg/l All rats survived at indicated concentration.
Acute LC50 (rat): > 12.9 mg/l
Ingestion Acute oral LD50 (rat): > 15,000 mg/kg

SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED

CONDITIONS AGGRAVATED: Persons with severe skin, liver or kidney problems should avoid contact or use.

CARCINOGENICITY: This product contains no carcinogenic substances.

SECTION 12. ECOLOGICAL INFORMATION

MAMMALIAN INFORMATION:

AQUATIC ANIMAL INFORMATION: No aquatic environmental information is available on this product. Environmental effects of the substance have not been investigated adequately.

MOBILITY: This material is a mobile liquid.

DEGRADABILITY: This product is partially biodegradable.

ACCUMULATION: Bioaccumulation of this product has not been determined.

SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste management options. Recycle / dispose of observing national, regional, state, provincial and local health, safety & pollution laws. If in doubt, contact appropriate agencies.

SECTION 14. TRANSPORT INFORMATION

DOT SHIPPING NAME: BULK: Paint Related Material, NOT DOT REGULATED
DRUM LABEL: None
IATA / ICAO: Paint Related Material Not Regulated
IMO / IMDG: Paint Related Material Not Regulated
EMERGENCY RESPONSE GUIDEBOOK NUMBER: NA

WBPTO1

SECTION 15. REGULATORY INFORMATION

EPA REGULATION: SARA SECTION 311/312 HAZARDS: Acute Health, Fire. All components of this product are on the TSCA list.

STATE REGULATIONS: THIS PRODUCT MEETS REQUIREMENTS OF SOUTHERN CALIFORNIA AQMD RULE 443.1 & SIMILAR REGULATIONS

COMPANY IDENTITY: PACKAGING SERVICE CO., INC
PRODUCT IDENTITY: CROWN PAINT THINNER NEXT
NEW MSDS DATE: 11/09/2007

DATE: 11/09/07
PAGE 4 OF 4

INTERNATIONAL REGULATIONS: The components of this product are listed on the chemical inventories of the following countries: Australia, Canada, China, Europe (EINECS), Japan, Korea, United Kingdom.

SECTION 16. OTHER INFORMATION

HAZARD RATINGS:

HEALTH (NFPA): 1 HEALTH (HMIS): 1 FLAMMABILITY: 0 REACTIVITY: 0

This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

EMPLOYEE TRAINING: See Section 3 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this MSDS) before handling it.

NOTICE: The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process. Unless updated, this Material Safety Data Sheet is valid until 11/09/2010.